

ATG ACCESS

ATG Access SP 400 Shallow Mount



The SP400 anti-terror/high security bollards are available as Automatic, Fixed, Shallow Mount, and Manually Retractable

The ATG Access SP400 Shallow Mount is part of the ultimate security bollard family. This product is designed to protect at the PAS68 level, and is able to stop a fully laden 7.5 tonne vehicle travelling at 30mph. This shallow mount fixed bollard only requires a civil installation depth of 170mm.

Traditional high security barriers require sizeable and deep foundations. While these are appropriate for many situations, there are often underground services and structures which prevent the use of these deep products.

The ATG Access shallow mount system is a revolutionary engineering development and sits at the cutting edge of industry technology. Shallow Mount is not linked to any particular product, it is a structure we have developed that enables us to provide high security products which can be installed at a fraction of the depth underground that traditional products require.

Shallow mount technology is the latest innovation in physical security and is proving invaluable within city centres, outside airports, skyscrapers and other places where underground services, car parks and basements prevent standard depth equipment to be installed.




ATG Access

CoBaCo House
North Florida Road
Haydock Industrial Estate
Haydock
Merseyside
WA11 9TP

www.atgaccess.com

Tel: 08456 75 75 74
Fax: 08456 75 99 55
Email: sales@atgaccess.com



ATG ACCESS

ATG Access SP 400 Shallow Mount

Characteristics

Product	Diameter	Height	Wall thickness	Finish	Foundation Depth
SP 400 Shallow Mount	203mm in black / or 219mm with Stainless Steel sleeve	1000 mm	Confidential	Sherardised black or stainless steel sleeve.	170mm (Standard Installation depth is 220mm inc. ground cover)

Technical specifications

Testing Criteria: BSI PAS 68 : 2010

Vehicle weight: 7.500kg

Vehicle speed: 48km/h (30mph)



Full PAS 68 Designation: 7500(N2)48/90:2.3/2.7

203mm Diameter on Sherardised finish.

219mm Diameter on stainless steel finish (sleeve).

The Benefits

- Impact tested in accordance with BSI PAS 68:2010, and equivalent to ASTM (DOS) K8 tested
- Modular design makes service and maintenance especially straightforward
- Full installation service or supply only
- Matching static, lift-out, manually retractable, and automatic bollards
- Manufactured in the UK



We can produce a written evaluation, in the form of a quotation, and provide draw photographs based on your requirements.

All details correct at time of going to press, ATG Access Ltd reserves the right to specifications, design, operating conditions or any other details without notice

ATG Access

CoBaCo House
North Florida Road
Haydock Industrial Estate
Haydock
Merseyside
WA11 9TP

Tel: 08456 75 75 74

Fax: 08456 75 99 55

Email: sales@atgaccess.com

www.atgaccess.com